

PRIMEX

Product Specifications

P750FCC-XGH2SA

1-2 Fiber Cross-Connect OSP Enclosure

1. SUMMARY

The Primex Wave P750FCC-XHG2SA is a mid-size two fiber cross-connect enclosure ideal for FTTH SFU and small business applications where slack storage is required.

The simplex SC/APC adapters and integrated cable management allow for the quick connection and storage in dual fiber applications.

2. DIMENSIONS

Inside: H 8.9"/W 5.9"/D 3.1"
Outside: H 12.2"/W 8.6"/D 3.9"

3. FEATURES & BENEFITS

- Mid-size cross-connect enclosure with slack storage for two fibers in FTTH and small business applications.
- Integrated fiber management and an SC/APC adapter for easy two fiber implementation.
- Snap lock and hex bolt provide secure service provider access 24/7.
- High quality UV-protected PVC made in North America for long-lasting fiber protection in demanding weather conditions.
- Two robust one-inch ports with grommets for protected fiber entry and exit.
- External wall and pole mounting brackets allow for quick and easy deployment.
- UL-listed and industry-standardized for easy implementation.

4. APPLICATIONS

- FTTH for single or multi family units
- FTTB for small businesses (MTU)

5. CONFIGURATIONS

Part #	Part Name	Description
125-1698	P750FCC-XHG2SA	Hex, gasket, 2x SC/APC, 2x grommets, 3x HClips, ground lug



FOR MORE INFORMATION CONTACT:

1.604.881.7875 1.604.881.7835

www.primex.com



primex  Fit everything. Together.