PRIMEXProduct Specifications

SOHOaccessTM **SAE-42**42" Metal Enclosure

1. SUMMARY

The Primex SOHO Access™ Enclosures provide a fast, flexible, and clean distribution management solution for wired security, voice, data, video, and audio connections. This feature-rich, ruggedized enclosure is designed to be either flush mounted between sixteen inch centered studs or surface mounted via recessed mounting holes.

2. PRODUCT DIMENSIONS

Inside: H 42"/W 14.25"/D 3.75" Outside: H 44.3"/W 16.5"/D 4.1"

3. FEATURES & BENEFITS

- Large internal space for installation of wired active, passive, and cable management components.
- Vertical and horizontal mounting hole pattern.
- Multiple entry/exit knockouts on top and bottom support microduct and robust cable runs.
- Multiple cable tie attachment points offering better, cleaner cable management
- Door covers provide a knock-out for a security lock.
- UL listed for security alarm and fire signalling applications.


*Enclosures should not be mounted in a fire-rated wall.

4. CONFIGURATIONS

Part#	Part Name	Description
135-0170	SAE-42NY	42" Metal Enclosure base
135-0169	SAE-42DDCNY	42" Metal Enclosure w/door cover
135-0160	SADDC-1428	42" Metal Dual Door cover
135-0089	SAM-EPM	Enclosure Partition Module







- 1. Fiber entry/exit points
- 5. Cable tie loops
- 2. Slotted screw mounts
- 6. Recessed screw mounts
- 3. Flush mounting tabs
- 7. 2.5" knock-outs
- 4. Flexible mounting tabs
- 8. 110 outlet knock-out

