

1. SUMMARY

The Wall Mount DSL Adapter mounts to an existing wall mount phone jack providing an unfiltered jack for your DSL connection plus one or two filtered lines for voice device communications (e.g. phone, fax, answering machine, Caller ID box) via two auxiliary phone jacks. Primex wall mount DSL filters isolate telephone equipment impedances from ADSL signals, delivering high bandwidth ADSL transmission capabilities.

2. DIMENSIONS

SIZE: Standard Wall Plate

3. FEATURES & BENEFITS

- Compatible with ADSL and ADSL2+
- Complies with Part 68 of the FCC Rules and the requirements adopted by the ACTA
- ANSI T1. 421
- Material is flame retardant thermoplastic compliant with UL 94V-0
- Filter topology: 2-pole low pass
- Contacts (plug and jacks) minimum 50 microinch of gold and nickel
- Customer installable

4. CONFIGURATIONS

Part #	Part Name	Description
135-0041	630LCCU-50	1-line wall mount adapter DSL filter (pins 3&4) w/ auxiliary unfiltered jack, ivory
135-0050	630LCCU-85	1-line wall mount adapter DSL filter (pins 3&4) w/ auxiliary unfiltered jack, white
135-0051	630LCCU-2F-50	2-line wall mount adapter DSL filter (pins 3&4, 2&5) w/ auxiliary unfiltered jack, ivory
135-0052	630LCCU-2F-85	2-line wall mount adapter DSL filter (pins 3&4, 2&5) w/ auxiliary unfiltered jack, white



FOR MORE INFORMATION CONTACT:

1.604.881.7875 1.604.881.7835

www.primex.com [f](#) [t](#) [in](#) [c](#) [y](#)