

**1. SUMMARY**

The 625A2 jack assembly series are surface mounted jack assemblies consisting of a snap-on cover and a base with an integral modular jack. Wire access is provided by a slot at the rear.

Installation time is reduced by eliminating the center cover retaining screw. Double-sided adhesive tape is included for mounting on desks, cabinets or wherever attaching with screws isn't ideal.

**2. DIMENSIONS**

SIZE: 0.97" H x 2.25" W x 2.31" L

**3. FEATURES & BENEFITS**

- Snap-on cover and factory wired for quick installation
- Double sided adhesive pad included for versatile mounting options
- Available with USOC RJ48X/RJ31X wiring for security alarm or life-line applications

**4. CONFIGURATIONS**

Part #	Part Name	Description
135-0310	625A28K-2-52	Jack Assembly; 8 - conductor, screw terminals, keyed, RJ48X shorting bar, Electrical Ivory
135-0328	625A28NK-2-50	Jack Assembly; 8 - conductor, screw terminals, non-keyed, RJ48X shorting bar, Ivory
135-0334	625A28NK-2-52	Jack Assembly; 8 - conductor, screw terminals, non-keyed, RJ48X shorting bar, Electrical Ivory
135-0332	625A28SB50	Jack Assembly; 8 - conductor, screw terminals, non-keyed, RJ31X shorting bar, Ivory



625A28K-2-52

Electrical Specifications	
Contact Pressure	>100 grams
Insulation Resistance	>500 megohms
Contact Resistance	<100 milliohms
Current/voltage	<140 VDC @ 2 amps



FOR MORE INFORMATION CONTACT:

📞 1.604.881.7875 📠 1.604.881.7835  
[www.primex.com](http://www.primex.com)