

## Universal Fiber Terminal

The Primex® Universal Fiber Terminal (UFT) delivers unmatched versatility and reliability for fiber-to-the-home (FTTH) installations. Designed as a universal splice enclosure, this compact yet robust solution enables technicians to patch, splice, and store fiber slack with ease.

Featuring six SC/APC adapters, integrated cable management for up to 50 feet of flat drop fiber, and dual entry/exit ports, the 6UFT simplifies installation while maintaining superior performance. Its arched, low-profile design not only enhances aesthetics but also improves water runoff and fiber routing, ensuring durability in all environments. Designed to GR771 Telcordia standards, the 6UFT is the ideal choice for residential deployments where functionality meets form.



### Features & Benefits

- Up to six SC/APC Adapters – Supports multiple connections for efficient FTTH distribution.
- Integrated Cable Management – Clamps are internally molded and form cables to the arch. Stores up to 50 feet of flat drop fiber, reducing clutter and improving serviceability.
- Dual Entry/Exit Ports – Enables quick drop cable installation and easy distribution cable connection.
- Splice Capacity – Accommodates up to six fusion splices for flexible configurations.
- 900µm Fiber Storage Cassette – Provides organized storage for buffer tubes and fibers. Removable tray snaps securely into place.
- Two Backwall Knockouts – Allows additional egress and entry into the customer's residence.
- Arched Aesthetic Design – Enhances curb appeal while promoting water runoff and fiber routing.
- GR771 Telcordia – Designed to industry standards for durability and reliability.
- Fiber Strain Relief Clamp – Adds stability and protects fiber integrity.
- Conduit Grommet Included – Simplifies conduit to enclosure connections for secure installations.
- Branded Design – Optional embossed logo capabilities for brand recognition and integrity.
- External Tracer Stud – External stud attaches tracer wire without opening NID for quick, secure installation.

### Dimensions

Inside: H 9.7" / W 9.2" / D 3.0"

External: H 12.7" / W 11.6" / D 3.6"

### Ordering Information

| P/N      | Model      | Description                              |
|----------|------------|------------------------------------------|
| 125-2407 | 6UFTSCAPC  | Universal Fiber Terminal, 6 Fiber SC/APC |
| 125-2409 | 05127ULCON | Conduit Pipe Adapter Grommet 1"          |
| 125-2408 | 05127UL    | Grommet 1" Groove                        |
| 125-2418 | 2UFT-SCAPC | Universal Fiber Terminal, 2 Fiber SC/APC |
| 125-2419 | 1UFT-SCAPC | Universal Fiber Terminal, 1 Fiber SC/APC |

## Universal Fiber Terminal

